



**DASMA**  
Door & Access Systems  
Manufacturers Association  
International

OPERATOR & ELECTRONICS DIVISION

# TECHNICAL DATA SHEET

## #360

1300 Sumner Avenue  
Cleveland, Ohio 44115-2851  
Phone: 216-241-7333 • Fax: 216-241-0105  
E-mail: [dasma@dasma.com](mailto:dasma@dasma.com)

## Placement of Gate Operator Controls

In many instances, automatically operated vehicular gates are opened and closed by means of permanently mounted controls in the vicinity of the gate. Controls include such devices as key switches, card readers, keypads and telephone entry systems, depending on the preference of the building/property owner and/or the type of security feature desired. Placement of these controls is extremely critical from a safety standpoint. The UL 325 standard includes some instructional requirements in Chapter 56 that installers of automated vehicular gates are strongly urged to follow. These requirements are as follows, with explanatory comments after each of the quoted requirements:

1. **“Gate operator controls intended for user activation must be located at least six feet (6’) away from any moving part of the gate and where the user is prevented from reaching over, under, around or through the gate to operate the controls.”**

“Intended for user activation” indicates the intent to move the gate. Reset buttons and other similar controls that do not move the gate do not fall under this requirement.

Six feet (6’) is the minimum distance required to provide protection for a person from being injured by a moving gate. This distance may need to be greater based on site specific conditions.

“Lock boxes” that may be required by local fire departments are frequently mounted near gates; therefore, safe use by fire department personnel must be provided as well.

2. **“Gate operator controls must be placed so that the user has full view of the gate area when the gate is moving.”**

This requirement only applies to gate operators that rely on Type D entrapment protection (use of continuous pressure controls to activate the gate). The user must see the gate during full operation to ensure no one is in the vicinity of the gate and thus potentially subject to contact with the moving gate.

---

**Note: Technical Data Sheets are information tools only and should not be used as substitutes for instructions from individual manufacturers. Always consult with individual manufacturers for specific recommendations for their products and check the applicable local regulations.**

This Technical Data Sheet was prepared by the members of DASMA's Operator & Electronics Division Technical Committee. DASMA is a trade association comprising manufacturers of rolling doors, fire doors, grilles, counter shutters, sheet doors, and related products; upward-acting residential and commercial garage doors; operating devices for garage doors and gates, sensing devices, and electronic remote controls for garage doors and gate operators; as well as companies that manufacture or supply either raw materials or significant components used in the manufacture and installation of the Active Members' products.

OPERATOR & ELECTRONICS DIVISION  
**TECHNICAL DATA SHEET**

**#360**

3. **“The Stop and/or Reset button must be located in the line-of-sight of the gate.”**

When the operator is to be stopped or reset, it is very important for the person doing the stopping or resetting to have a full, clear view of the gate system to ensure that the cause of any entrapment protection device activation has been removed from the path of the moving gate prior to resetting the gate for further activations.

4. **“Outdoor or easily accessible controls shall have a security feature to prevent unauthorized use.”**

Sometimes it is necessary to protect controls on the side of the gate accessible to the general public. When gate access needs to be protected, controls used should be protected or secured. Controls can be secured via keys, keypads or other access control systems.

**A PERSON SHOULD NEVER BE ALLOWED TO “REACH THROUGH” A VEHICULAR GATE TO INITIATE OPERATION. THIS IS AN EXTREMELY DANGEROUS SITUATION AND SHOULD BE PREVENTED BY PROPER PLACEMENT OF GATE OPERATOR CONTROLS.**

---

**Note: Technical Data Sheets are information tools only and should not be used as substitutes for instructions from individual manufacturers. Always consult with individual manufacturers for specific recommendations for their products and check the applicable local regulations.**

This Technical Data Sheet was prepared by the members of DASMA's Operator & Electronics Division Technical Committee. DASMA is a trade association comprising manufacturers of rolling doors, fire doors, grilles, counter shutters, sheet doors, and related products; upward-acting residential and commercial garage doors; operating devices for garage doors and gates, sensing devices, and electronic remote controls for garage doors and gate operators; as well as companies that manufacture or supply either raw materials or significant components used in the manufacture and installation of the Active Members' products.