

Garaga Announces New Cambridge Design

In December, Garaga introduced a new steel garage door inspired by the high technology and old-world charm of Cambridge, Mass.

The Cambridge has recessed panels with woodgrained overlays and is available in five panel colors, three overlay colors, and window options that replicate traditional wooden door windows.

Polyurethane foam is pressure-injected between steel walls to create a lightweight composite material with improved insulating qualities, rigidity, and durability. www.garaga.com ■



Overhead Adds Premium Residential Wood Doors

In January, Overhead Door introduced its new Signature Carriage Collection of custom premium wood doors for upscale homes.

Each door is hand-built by Amish craftsmen in Mt. Hope, Ohio. Signature Collection doors feature the swing-open carriage house style and are hewn from cedar, hemlock, and mahogany. Each door is available with standard or customer-specified features, including wood species, sizing, construction style, window style, patterns, paint or stain finish, and hardware. www.overheaddoor.com ■



Amarr Now Offers Residential Full View

In November, Amarr introduced the Vista Collection of aluminum full-view garage doors.

The Vista Collection offers a sleek, modern look that creates a sense of more space in the garage, says Vickie Lents, marketing director. She adds that the doors can also be used as interior room dividers.

The Vista Collection features 2"-thick extruded commercial-grade aluminum frames that provide durability, low maintenance, and corrosion resistance. The doors are available in clear anodized aluminum, white, bronze, black, or custom powder coat finishes and include modern-looking exterior handles.

The Vista Collection also includes 1/8" tempered glass and comes in transparent, opaque, textured, or tinted glass options. A variety of additional colors, insulated tempered glass, and additional wind load protection also are available. www.amarr.com ■



Northwest Door Adds New Carriage Door Model

In January, Northwest Door introduced the new Therma Tech T10C, a new carriage-style door with a 1-1/2"-thick steel sandwich construction, a polystyrene core, and a true thermal break for an R-Value of 7.2.

Options include 12 window designs and four standard colors. For ease of installation and door operation, doors are made with standard 18"- and 21"-high sections. Door sizes range up to 20' wide and 14' high. www.nwdusa.com ■



Overhead Door Expands FireKing Fire Doors

In December, Overhead Door announced its newly expanded commercial line of FireKing Fire Doors.



The doors use a floor reset hoist system for easy drop testing and resetting. Spring tension resetting and sash chain rerouting are no longer required.

FireKing Fire Doors have up to a four-hour fire rating on masonry, concrete, and steel walls and up to a three-hour rating on non-masonry walls. The doors meet the requirements for UL, ULC, FM, NFPA 80, New York City, and California. Options include

UL-labeled smoke seals, Fire Sentinel fire door release system, FM-approved flame baffle, FireLite vision lite, horns, strobes, and smoke detectors.

Unlike other brands, FireKing Insulated Fire Doors feature mineral wool insulation compressed within the slats for sound control.

www.overheaddoor.com ■



Clopay Adds Roll-Up Sheet Doors

In February, Clopay introduced the Model 157C mini warehouse and commercial roll-up sheet doors in a corrugated steel panel design.

Designed to fit openings up to 12' by 14' and available in 19 standard stock colors, the Model 157C is designed for fast installation, durability, and low maintenance. Insulation is optional.

Its 26-gauge galvanized steel curtains are interlocked and seamed together for the full height of door. A 16-gauge universal guide design allows the doors to be mounted directly to wood, steel, concrete, or masonry block without any modification to the jambs.

The paint system is backed by a 40-year warranty against cracking, checking, or peeling, and a 25-year warranty against fading or chalking. www.clopaydoor.com ■



DBCI

THE FREIGHT INDUSTRY'S CHOICE FOR FACILITY DOORS

www.dbci.com | 877.928.1333

Rolling Sheet Door Revolution

Fast & Easy Install - Cost Effective
World Class Customer Service



Less Expensive
Compared To Traditional Freight Facility Doors

Hörmann Flexon Enhances Speed-Master and Speed-Commander

In February, Hörmann Flexon enhanced its Speed-Master 1600 L and Speed-Commander 1400 SEL with a light grid built into the guide tracks up to 8'0" high. Free of coil cords, the light grid provides a thorough wall of protection, compared to doors that use only photo cells.

The two enhanced models now accommodate the standard power sources readily available in most facilities. In addition, the Speed-Master 1600 L now has guide tracks with removable covers. Heavy-duty 12-gauge galvanized steel tracks are a two-piece design, and the front covers open for easy resetting.

The Speed-Commander 1400 SEL now comes in sectional panels connected with aluminum profiles designed for fast replacement.

www.Hormann-Flexon.com ■



Great Northern Door Announces Upgrades

In January, Great Northern Door announced upgrades to its Craftsman Series Doors.

The doors now come standard with stain grade, 1/4" hardboard interior panels. In addition, the doors now include 1-1/4" polystyrene insulation and come in Douglas fir, western red clear cedar, and western red knotty cedar.

www.greatnortherndoor.com ■

continued on page 12

Insulated panels aren't the future, they are NOW! Are you operating in the NOW? Bradbury offers continuous and discontinuous equipment options for production of insulated metal, plastic, and fiberglass doors.

Bradbury Group Australia's Solid Core Continuous Line



BRADBURY GROUP
Australia

Bradbury USA's PU & PIR Continuous & Discontinuous Lines



BRADBURY

www.bradburygroup.com

620.345.6394

bradbury@bradburygroup.com

See us at IDA Expo Booth #5019, Indianapolis, IN, June 3-4, 2011

Dual Tite Launches New Garage Door Seals

In February, Dual Tite Seals announced that it would introduce two new sealing products at Expo 2011. Both products feature Dual Tite's proprietary soft seal material and are patent pending.

The first product is the DTVV Dual, a dual-flap door stop with a 2" body and a 1" and 1-1/4" sealing flap. The dual flap helps reduce thermal conductivity, noise, and sun glow. The flaps also have a ribbed back to prevent sticking. DTVV Dual is available in most standard sizes and colors.

The Dual Universal bottom seal fits doors from 1" to 2" thick. Replacing eight different bottom seals with one universal seal, it reduces a dealer's inventory and reduces costs. www.isotrude.com ■



Janus Introduces New Certified Wind Load Door

In February, Janus International announced Model 3652, a new certified wind load sheet door with nylon windlocks. During wind load testing, the door exceeded expectations.

Its nylon windlocks offer an easier installation process and smoother operation. Nylon windlocks also call for smaller guides and no separate windbar.

"Other doors have required five windlocks to our three and achieved lesser certified pressures than the Model 3652," says David Curtis, president. "This door will be of significant value to our customers in Florida, North Carolina, Texas, and other wind load-coded areas." www.janusintl.com ■



Goff's Releases New Operator

In January, Goff's released a new 36"/sec. solid state operator control that allows for a quicker setup and easier installation.

The new Goff's/Manaras operator features status integrator LEDs for easier troubleshooting, an integrated auto-close timer, and a proprietary soft-start function. The motor works in conjunction with Goff's new G2 door line of high-speed roll-up doors. www.goffdoors.com ■

Your **RE-SOURCE** for Flood Vents FOR GARAGE DOORS

- FEMA Elevation Certificate requires evidence that flood prone enclosed areas are vented properly to permit hydrostatic water pressure equalization
- Each Smart Vent® protects up to 200 Sq. Ft. of area below the Base Flood Elevation (BFE). Use fewer vents, and improve home protection
- Flood Insurance rates increase dramatically if no vents or non-compliant vents are used in areas below the BFE
- ICC-ES Evaluated, FEMA Accepted and approved by the Florida Building Code Commission



Insulated and Dual Function models available



Re-Source Industries, Inc. ■ Fort Worth, Texas ■ TOLL-FREE Order Line: 1-866-316-7337 ■ www.re-sourceind.com ■ FAX 817-222-9950