



### Clopay adds new models to glass door line

In January, Clopay Corporation added the new residential Avante Sleek model and commercial models 905 and 906 to their modern glass garage door line. The sectional overhead doors feature horizontal tempered glass or acrylic panels with minimal stiles for unobstructed views with plenty of natural light.

Single-car doors up to 10'2" wide have no center stile, double doors have one center stile, and doors up to 22'2" wide have two equally spaced vertical stiles. 12 window options and multiple frame colors are available.

An integrated bulb seal between the tongue and groove section joints keeps out air and water. The new doors meet ASHRAE 90.1 and IECC air filtration requirements and insulated models comply with HFC-free mandates.

[www.clopaydoor.com](http://www.clopaydoor.com) ■

### AkzoNobel announces coatings for HVAC market

In January, AkzoNobel highlighted their new Polydure coatings – the N V1000 and N V1000

TX – with a resin technology specifically designed for the HVAC segment, including commercial, industrial, and residential applications.

The coating system features a consistent smooth film and excellent forming properties, provides batch consistency, and is offered in a broad range of color, gloss, and texture options.

The N V1000 standard coating is formulated with UV inhibitors and edge-coat corrosion resistance and is designed for exterior and interior applications. The N V1000TX textured specialty coating is formulated with UV inhibitors and is designed for scratch and abrasion resistance, which makes it ideal for textured surfaces of exterior and/or interior applications. [www.akzonobel.com](http://www.akzonobel.com) ■



### Overhead Door unveils new commercial storm shelter doors

In January, Overhead Door launched EverGuard Rolling Steel Storm Shelter Doors – their first line of commercial rolling-steel, storm-shelter doors designed to provide protection against severe weather, fires, and forced entry. The new doors are ideal for schools, emergency operations centers, storefronts, saferooms, and other facilities.

The EverGuard series meets stringent safety and shelter design standards, ensuring that these buildings are protected in times of emergency, and feature heavy-duty 12-gauge curved slats, with free-acting interlocking joints, that provide a natural watershed and help reduce corrosion. They also include a double-angle bottom bar and a spring barrel that encases the counterbalance mechanism.

[www.overheaddoor.com](http://www.overheaddoor.com) ■



### Weathered Gray now available in Amarr Classica Collection

In February, Amarr introduced a new Weathered Gray woodgrain color option for its Amarr Classica and Classica Full View collections of garage doors. The on-trend, versatile gray color can be paired with any exterior home design. These carriage house and modern designs are combined with durable, low-maintenance steel construction and modern functionality to enhance curb appeal. [www.amarr.com](http://www.amarr.com) ■



## Miller Edge releases new photo optic system

In January, Miller Edge introduced the new OptiGuard (OG-T-K10) monitored thru-beam photo optic system. OptiGuard is a UL 325-recognized photo-eye that delivers entrapment protection for door and gate operators.

Equipped with an operating range of 100 feet and IP67 protection against a variety of weather conditions, OptiGuard offers both normally closed and 10K outputs and allows for easy installation and quality safeguarding for commercial motorized doors and automated vehicular gates.

The OptiGuard is available through the Miller Edge customer portal, MyEdge, and local distributors. [www.milleredge.com](http://www.milleredge.com) ■

## The HySecurity SlideDriver II has launched

In February, Nice introduced the next generation of the SlideDriver from HySecurity — SlideDriver II. The new slide gate operator builds upon the original SlideDriver and offers the new SmartTouch 725 controller.

Additional features include simplified setup with the HySecurity Installer app, Bluetooth and integrated HyNet capabilities, built-in diagnostics and remote configuration, contactless limit sensors, adaptive inherent entrapment sensors, and more than 70 user settings. [www.hysecurity.com](http://www.hysecurity.com) ■



## GateArms highlights LED safety light system

In January, GateArms featured the Brink Alert LED-illuminated Door Safety Kit (DSK). The DSK universal LED light system wires into any existing operator and is designed for firehouses, cold storage units, and other commercial or industrial applications with overhead doors. The company's patented LED Controller receives the open and close signals from the door operator and responds by changing the colors of the LEDs (IP68-Rated). [www.gatearms.com](http://www.gatearms.com) ■

## Clopay introduces LED Light Kit for rolling doors and grilles



In February, Clopay Corporation introduced an LED-illuminated Light Kit for its Cornell Cookson brand of rolling doors and grilles to help prevent damage, downtime, and costly repairs to fire and EMS stations, warehouses, and parking garages.

The highly visible LED strip lights easily mount to the door guides. The lights turn solid red when the door is closed and flash when in motion or if the operator loses power. Solid

green lights indicate when the door is fully open. White LEDs notify when the door's safety device triggers or photo-eye malfunctions.

The double-sided kits are available for back-in stations (inside and outside) in 5', 10', or 15' systems and can be retrofitted or installed on new standard and high-performance rolling doors, grilles, and counter doors, excluding fire and smoke-rated products. [www.clopaydoor.com](http://www.clopaydoor.com) ■

## Hörmann North America introduces low headroom direct-drive rubber door

In December, Hörmann North America added the HD-DD 2555 to their HD series of rubber doors. The new model has only 20" of required headroom, which is ideal for retrofit installations with limited clearance. The springless, direct-drive system door is simple to install, requires little maintenance, and performs well in rugged environments where high-speed operation is required.

Designed for door openings up to 25' x 17', with opening speeds up to 55" per second, depending on the door size, the HD-DD 2555 is ideal for applications such as transit, airport, and rail maintenance shops.

A variable-frequency drive motor provides soft starts and soft stops. The door comes with five- and two-year warranties. Maximum recommended cycles are up to 500 cycles per day.

[www.hormann.us](http://www.hormann.us) ■

